

Flexi Screen Ultra

ACCESSORIES LINE



Packing Information

Each unit - 385 x 295 x 345 mm*

Units per box - 1

Box - 445 x 335 x 400 mm

Box Gross Weight - 1.83 Kg

*Please notice that the dimensions of this panel have a tolerance of +/- 3 mm

FEATURES

Flexi Screen Ultra is the ideal portable solution for vocal recording in untreated rooms, or venues which lack sufficient acoustic control. It performs on untreated and scattered room reflections, effectively isolating the sound source.

Flexi Screen Ultra is made from high quality materials. Its polyurethane structure is designed to give maximum absorption efficiency. The addition of wood to the exterior surface helps create a barrier and gives an attractive visual effect. The singer's energy is absorbed on the inside of the unit, producing a dryer, less ambient sound. At the same time, scattered room reflections are treated on the outside.

Flexi Screen Ultra can be used with a range of microphones and can be adjusted either horizontally or vertically.

APPLICATIONS

Voice and instrument recording

TECHNICAL INFORMATION

Material: Polyurethane Foam

Fire Rating:

Foam: M1 (NF P 502-94 and NF P 502-95)

Euroclass F (ISO 11925-2:2010)

Product Classification: Euroclass F (ISO 11925-2:2010)

