## PIR CAMERA BUILT-IN IR SENSOR WITH OSD





## **FEATURE**

- 1/3" Sony Super HAD II Color CCD Sensor achieves impressive performance of high sensitivity
- Built-in IR sensor
- Excellent Picture Performance with Hi-resolution
- Apply to Home Security, Office, School, Supermarket, Restaurant, Government Building, Bank, Hotel

## **SPECIFICATION**

Model No.	PIRCAMH/I	
Lens	4.3 mm	
Color CCD	1/3" Sony Super HAD II Color CCD Sensor	
System	NTSC / PAL	
SYNC System	Internal	
Number of Pixel	NTSC: 811 (H) x 508 (V) PAL: 795 (H) x 596 (V)	
Resolution	600 TV Lines	
PIR Detection Angle	Horizontal = 100° / Vertical = 45°	
PIR Detection Range	10 M	
PIR N.C/N.O Relay	1A / 120VAC, 2A / 30VDC	
PIR N.C/N.O Alarm	Adjustable from 2 to 50 sec	
Minimum Illumination	0.1 Lux	
S / N Ratio	More than 48 dB	
Electronic Shutter	1/60 ( 50 ) to 1 / 100,000 sec.	
Gamma Correction	0.45	
White Balance	Auto (ATW)	70
AGC	Automatic	
BLC	Automatic	
<b>Current Consumption</b>	80mA ± 10%	
Working Voltage	DC 12V	
Video Output	1.0 Vp-p Composite, $75\Omega$	
Scanning Frequency	15.734 KHz (H), 59.94 Hz (V) ( NTSC )	<u>30                                 </u>
Operation	-10°℃ ~ 60°℃	<del></del>

Designs and specifications are subject to change without notice.