

5MPV-PO

Outdoor Fisheye Network Camera

5MP Panoramic View



Features

- 5-Megapixel CMOS Sensor
- 15 fps@1920x1920 Full HD
- Dewarping the Image via Fisheye Correction Processor
- Removable IR-cut Filter for Day & Night Function
- Real-time H.264, MPEG-4, and MJPEG Compression
- ROI (Region of Interest) Provide for 5 Independent Streams
- Minimum 0.1 Lux for Night Vision
- WDR Enhancement for Visibility in Extremely Bright or Dark Environments
- Two-way Audio Communication, External Microphone Input and Audio Output
- Built-in MicroSD Card Slot, support SDHC/SDXC 64GB or above
- Weather-proof IP66-rated Housing
- Built-in 802.3af Compliant PoE
- ONVIF Compliant for Interoperability



360° Broad View



360° Source View




Quad View



3 PTZ with Source View

System Information

Model No.	5MPV-PO	Interface	10 Base-T/100 BaseTX Ethernet(RJ-45)
CPU	Multimedia SoC (System-on-Chip)	ONVIF	Ver. 2.2
NOR Flash	16MB	Intelligent Video	
RAM	512 MB	Motion Detection	Ten-window video motion detection
Camera Features		Alarm and Event	
Image Sensor	1/2.5” Progressive CMOS sensor in 2592 x 1944 resolution	Alarm Triggers	Video motion detection, manual trigger, digital input, periodical trigger, system boot, recording notification
Maximum Resolution	1920x1920	Alarm Events	Event notification using digital output, HTTP, SMTP, FTP and NAS server File upload via HTTP, SMTP, FTP and NAS server
Lens Type	Fisheye Fix Lens		
Focal Length	f=1.05 mm		
Aperture	F= 2.8	General	
Field of View	180° (Horizontal/Vertical/Diagonal)	Connectors	RJ-45 cable connector for Network/PoE connection Audio input Audio output DC 12V power input Digital input*1 Digital output*1 Video output*1 (NTSC/PAL)
WDR Technology	WDR Enhanced	Power Input	DC 12V IEEE 802.3af PoE
Day/Night	Removable IR-cut filter for day & night function		
Minimum Illumination	1.9 Lux @F2.8 (Color) ; 0.1 Lux @F2.8 (B/W)		
Pan/Tilt/Zoom	ePTZ: 10x digital zoom	Power Consumption	Max. 5.1 W (DC 12V) Max. 5.3 W (PoE)
On-board Storage	Built-in MicroSD card slot, support SDHC/SDXC 64GB or above	Casing	Weather-proof IP66-rated housing
Video		Dimension	Ø:140 x 78.4mm
Compression	H.264, MJPEG & MPEG-4	Weight	Net: 970g
Display Mode	360° Source View, 360° Broad View, 180° Double Broad View, Triple View, Quad View, 3 PTZ with Source View	Safety Certifications	CE, FCC Class B, LVD
Maximum Frame Rate	15 fps at 1920x1920	Operating Temperature	0°C ~ 50°C
	15 fps at 1920x1080	Operating Humidity	10% ~ 80%
	30 fps at 1600x1200 (HI-FPS Mode)	System Requirements	
	30 fps at 640x480	Operating System	Microsoft Windows 7/Vista/XP/2000
Maximum Streams	5 simultaneous streams at ROI Mode 3 simultaneous streams at Normal Mode	Web Browser	Mozilla Firefox 7 ~ 10, Internet Explorer 7.x or 8.x, Chrome / Safari 4.0 or above
S/N Ratio	Above 39 dB	Other Players	VLC: 1.1.11 or above
Dynamic Range	100 dB	Included Accessories	
Video Streaming	Adjustable resolution, quality and bitrate ROI (Region of Interest) Provide for 5 Independent Streams	Quick installation guide, screws pack, software CD, mounting bracket (Optional)	
Image Settings	Adjustable image size, quality and bitrate Configurable brightness, saturation, exposure control, sharpness, contrast, white balance, auto shutter control, auto gain control, noise reduction, EV luminance control, flip & mirror, privacy masks, time stamp, text overlay	Dimensions	
Audio			
Audio Capability	Audio input/output (full duplex)		
Compression	G.711u		
Interface	External microphone input		
Effective Range	5 meters		
Network			
Users	Live viewing for up to 10 clients		
Protocols	HTTP,HTTPS, TCP/ IP,IPv4, UDP, SMTP, FTP, DHCP, DDNS, NTP, DNS, ARP,RTSP, RTP, UPnP, ONVIF(Profile S), Multicast		

➤ Designs and specifications are subject to change without notice.