

2.0 Megapixel PTZ Camera



Features

- 5-50mm 10X optical zoom Lens
- 4.5" Mini HD-IP High Speed Dome Camera
- Weatherproof Outdoor IP66
- Pan Range: 0°~360° Continue; Tilt Range: 0°~90° Flip
- Pan Speed: 200°/sec; Tilt Speed: 100°/sec
- Preset Points: 220
- Guard Tours: 3 Groups
- Guard Points: Max.16 points
- RS485, Protocol TCP/IP, HTTP, FTP, RTSP Support
- OSD Menu Available, P2P Support
- Power Adaptor: DC12V/3A
- Lightning Protection: Transient Voltage 6000V

Specifications

Model	2MZ-SPZ550F29
Camera	
Image Sensor	1/2.7" Low Illumination 2MP CMOS Sensor
Effective Pixels	1080P(1920*1080)
Total pixels	2.0 Megapixels
Output Pixel	1920*1080(@30fps@25fps); 1280*720(@50fps@60fps)
D/N	IR-CUT
BLC	Auto
WB	Auto
S/N Ratio	>50dB
Lens	
Lens	10X optical zoom f=5mm(W) ~ 50mm(T) ±5%
Iris	F1.6 ~F2.8
View of Angle	H: 51.8° (W) ~5.86° (T) V: 39.1° (W) ~4.4° (T)

Min. illumination	Color: 0.01 Lux \ B/W: 0 Lux
Camera Features	
Communications Protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP,
Software Control	IE, CMS
Mobile View(optional)	Support iOS, android
PTZ	
Horizontal Rotation Speed	0.02 ~200°/s
Horizontal Rotation Range	360°
Tilt Rotation Speed	0.02 ~120°/s
Tilt Rotation Range	93°
Preset Points	220
Guard Tours	4 groups
Guard Points	Max.16 points, dwell time user selectable
Operating temperature	Indoor: 0°~ +40°; Outdoor: -40°~ +60°
Operation menu	English
General	
Pan and Tilt position display	Support
Humidity	≤95% Non Condensing
Related validation	IP66,CE,FCC,RoHs
Operation menu	English OSD
Power	DC12V ≤3A
Consumption	< 22W
Lightning Protection	Transient voltage 6000V
dimensional	(LxWxH): 28x32x20(cm)
Size/Weight	2.7KG (N.W) , 3.4KG (G.W)

➤ Designs and specifications are subject to change without notice.