

2M Mini PTZ Dome IP Camera



Features :

1. Outdoor PTZ type in palm-size with unique interior IR Led and full function of I/O interface
2. Support Auto focus / Smart focus / Step focus
3. Support advanced setting of WDR, 3D NR, ROI, Auto Iris, Low lux mode, Exposure control
4. Support H.264 / MPEG4 / MJPEG multi-codec and multi-streaming
5. Support connectivity with iPhone, smart phones and all browsers including IE, Firefox, Chrome, Safari and Opera
6. Support 2 way audio
7. Built - in Micro SD Card slot for easy storing and playback image/video
8. Built - in Samba function for storing image/video at local area network directly
9. Built - in Motion Detection & Email Notification
10. 3X optical zoom , 4X digital zoom
11. Up to 30 fps at 1920 x 1080 of video resolution

Specifications

Model No.	MINIPTZD-IP2MD129
Camera	1/2.8" Sony CMOS sensor, Resolution: 1920x1080
IR Led	Auto/Manual mode, above 20 meters visible
	Spectral band width 42nm, Peak emission wavelength 850nm
	Daylight sensor, angle +/-65, wave length 400~700nm
Lens	3X optical zoom lens, auto iris, auto focus
	f = 3mm ~ 9mm, F1.8 Fov(D), 136° ~ 39°
Protocol	TCP/IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, PPPoE, DNS, DHCP and RTSP
Video Resolution	Up to 30 frames at 1920*1080, 1280x1024, 1280x800, 640x480, 320x240 and 176x144
Algorithm supported	H.264/MPEG4/MJPEG multi-codec for streaming video, JPEG for still image
Physical	10 baseT or 100 baseT Fast Ethernet auto negotiation
Audio	G.711/AMR/AAC
	Omni-directional Microphone
	Support 2 way audio

Pan/Tilt angle	Support auto tracking function
	Support multi - direction movement
	Pan : 250° Tilt : 75°
Power	12VDC, 1.5A
	Consumption: Max 10 W
	Support 802.3af compliant Power over Ethernet
I/O Interface	RJ-45
	DI
	DO
	Mic. in
	Audio out
	DC Power
	Micro SD Card Slot(inside camera)
EMI & Safety	CE, FCC
Dimension	Height : 72.5mm, Diameter : 93.8mm(excluding 3 mounts)
Operating Environment	Temperature : -5 ~ 50°C
	Humidity : 85% RH
Weight	NET. 460g

➤ Designs and specifications are subject to change without notice.