

1.3MP IR DOME IP Camera

NiMAX[®]



Feature:

1. 1/3" 1.3Mega progressive scan CMOS
2. H.264 960p realtime recording
3. Support intrusion detection
4. 2D/3D DNR, DWDR, Anti-fog, IR_CUT
5. Dual-Stream, Mobile APP, Support P2P
6. Support PoE, Support reset button
7. Support ONVIF

Specifications:

Model No.	1MF-IRD16D134
Sensor	1/3" 1.3Mega progressive scan CMOS
Min.illumination	Colour:0.01Lux/F1.2; 0Lux/F1.2(IR ON)
Lens	3.6mm M12 lens, 2.8mm/6mm/8mm optional
IR distance	20 M
Electronic shutter	Auto(1/10s-1/10000s Adjustable)
Day/Night	Auto/Color / B&W (IR_CUT)
Noise Reduction	2D/3D Digital Noise Reduction
Anti-fog	Support
WDR	Digital WDR
Image Adjustment	Sharpness,Brightness,Saturation,Contrast Adjustable
Video Encoding	H.264
Encoding Type	High Profile/Main Profile/BaseLine Profile
Record Resolution	Main Stream : 1280*960@25/30fps Sub Stream : 704*576@25/30fps
Video Bitrate Control	Support VBR/CBR
Video Bitrate Range	192Kbps~8Mbps
Reset Button	Front set reset button
Network Interface	RJ45 10M/100M adaptive Ethernet interface
Motion Detection	Multiple detection zones, variable sensitivity levels
Privacy Masking	Four zones for privacy masking
Snapshot	JPEG capture,capture resolution is the max coding resolution
Security Features	Support password protection, watermarking features
Text Overlay	Support (Channel name and time title)
Alarm	Support network anomaly,mask alarm and etc.
Intelligent Function	Support line-crossing detection
Mobile APP.	IOS, Andriod
Network Function	TCP/IP; UDP; HTTP; IGMP ; ICMP; DHCP; RTP/RTSP; DNS; DDNS; FTP; NTP;
Protocol	Support ONVIF and CGI protocol
Power	DC 12V
Operation Temperature	-10℃ ~ +60℃
Operation humidity	10%--90%
Power supply	3W MAX
Dimensions	114.6 x 88 (mm)
Weight	280g