

2.0 Mega Pixel IP IR Bullet POE Camera **NiMAX**[®]



1-Power Supply 2-network interface

FEATURES:

1. Economical HD IP IR cylinder camera
2. H.264 High Profile/Main Profile/ BaseLine Profile
3. 1080P full real time recording
4. Conforms to ONVIF, Support P2P,UPNP
5. Mobilephone, IE, Client Software, Platform Management Software Surveillance
6. Support Regional intrusion detection and line-crossing detection
7. Snapshot, email sending function, Auto ICR

Specifications :

Model No	2MF-BLP30D134
System	
Sensor	1/2.8"2.0Mega progressive scan CMOS
Min.illumination	Colour:0.01Lux/F1.2; 0Lux/F1.2(IR ON)
Video Parameters	Support WDR,Mirror,WB,3D Digital Noise Reduction,
Electronic shutter	Auto(1/10s-1/10000s Adjustable)
Day/Night	Auto/Color / B&W(IR_CUT)
Lens	3.6mm M12 lens
IR distance	20-30 m
video encoding	H.264 High Profile/Main Profile/BaseLine Profile
record resolution	1920×1080,1280×960,1280×720,704×576,352×288
Dual-stream	Support
Privacy Masking	Four zones for privacy masking
Capture	JPEG capture, capture resolution is the max coding resolution
Motion Detection	Multiple detection zones, variable sensitivity levels
Security Feature	Support password protection, watermarking features
Intelligent Function	Support Regional intrusion detection and line-crossing detection

Alarm	Support network anomaly, mask alarm and etc.
Video bite rate	32Kbps-12MKbps continuously-adjustable, support VBR/CBR
Data transmission and storage	
Data storage type	Record (video),picture file
Storage	Manual, auto(timing, motion detection, alarm)
Protocol/Network function	TCP/IP,UDP,HTTP,DHCP,RTP/RTSP,DNS,DDNS,FTP,NTP,PPPOE,UPNP,SMTP,SNM
Web Browser	IE, Safari, Chrome, Firefox, etc.
Mobile Surveillance	Iphone, Andriod
Interface	
Network interface	RJ45 10M/100M adaptive Ethernet interface
POE function	Support
Power	POE
Environment	
Operation temp./humidity	-10℃- +60℃/10%-90%
Power supply	≤5.5W
Dimensions	62*62*155(mm)
Weight	530g

➤ Designs and specifications are subject to change without notice.