

PM-2 Two-way Performance Monitor

The PM-2 compact monitor offers extraordinary tonal fidelity, effortless dynamic expansion and natural, almost holographic illumination into the deepest corners of the soundstage.



Look at them curves!

The elegant curvature of the enclosure is more than a design affectation. The specific geometry of the cabinet eliminates internal standing waves, because reflections between boundaries are never in synchronism. Enclosure geometry is carefully calculated so that any vibration in the front baffle is immediately transferred to the rear where it is absorbed harmlessly in the rounded back profile integrated into the enclosure specifically to provide additional mass loading to aid in damping resonance and vibration.

Powerful Motors

PM-2 employs Gato Audio's exclusive versions of the now legendary Danish developed 38 mm Ring Radiator high frequency transducer and bass/midrange driver. This much praised driver design is employed in some of the world's most expensive High End loudspeakers and is universally acclaimed for its accuracy, detail retrieval and efficiency.



Features:

- 2 way system
- Bass reflex construction
- Magnetically attached driver grills
- Stand mount secured with screws



Technical stuff

Frequency response 50 Hz – 25kHz (-6dB)

Sensitivity (2,83v) 89dB

Recommended power amplifier 50 to 300Watts

Nominal impedance 4 ohm

Connectors Gold plated 4mm Plugs, bi-wire

Drivers

High Frequency 38mm ring radiator, powerful ferrite motor and optimised chamber

Mid & Low Frequency 170mm paper cone. low loss suspension, motor with shorting rings and optimised voice coil

Weight & Dimensions

Weight 11 Kg / 24.25 lb

