


FM-6 2½ -way Fidelity Monitor



The 2 way FM-2 stand mounted loudspeaker is designed to bring unequaled musical performance in small to medium sized listening rooms.



Resonance Eliminating Program

The FM-6 incorporates several technologies of Gato Audio's proprietary Resonance Eliminating Program, such as solid aluminium resonance-breaking cabinet back profile, solid laminated curved cabinet, cut-cone, low Q electrical crossover design with components casted in resin.

Resin Casted Crossover

Top-class crossover such as huge low-resistance insatiable inductor coils, costly Clarity Cap and induction-free power resistors are mounted on thick fiber-glass PCB and then casted into resonance dampening resin.



Danish Dynamite

The best of Danish drivers have been selected, modified and adopted in the final design. A 180 mm bass/midrange driver with cut cone technology and optimised magnet system, works in perfect unison with the tweeter: A 38 mm high frequency Ring Radiator with extremely powerful neodymium magnet system and carefully designed waveguide ensures flat ultrasonic frequency response and effortless dynamics.



Features:

- 2½ way system
- High order, low Q crossover
- Bass reflex construction
- Magnetically attached driver grills
- Adjustable spike system, with locks and floor savers



Technical stuff

Frequency response	38 Hz – 30kHz (-6dB)
Sensitivity (2,83v)	90dB
Recommended power amplifier	50 to 300Watts
Nominal impedance	4 ohm
Connectors	Gold plated WBT binding post / 4mm Plugs, bi-wire
Drivers	
High Frequency	30mm Ring Radiator, Neodymium Motor
Mid & Low Frequency	180mm Sliced Cone, SD-1 Motor, Optimized Voice Coil
Low Frequency	180mm Sliced Cone, SD-1 Motor
Weight & Dimensions	
Weight	30 Kg / 66.14 lb

