

28CM ROUND MIRROR CAMERA WITH OSD FUNCTION



FEATURE

- Patent: The design of CCTV Camera behind the Mirror without pinhole on the surface
- Special Coating Technology
- Patent: OSD Function operated by Cable or Remote Control (optional) (Adjust the parameters of camera easily!)
- Apply to School, Supermarket, Convenient Store, Shopping Mall, Restaurant, Government Building, Bank, Hotel, Hospital, Bus/Train Station, Airport, Parking Lots, Lane
- 1/3" Sony Super HAD II Color CCD Sensor

SPECIFICATION

Model No.	CMRL2H
Built-In Lens	4.3mm (Available for 3.6, 6, 8, 12, 16mm Lens)
Color CCD	1/3" Sony Super HAD II Color CCD Sensor
Lens Angle	78°
System	NTSC / PAL
SYNC System	Internal
Number of Pixel	NTSC : 811 (H) x 508 (V) PAL : 795 (H) x 596 (V)
Resolution	600 TV Lines
Minimum Illumination	0.1 Lux
S / N Ratio	More than 48 dB
Electronic Shutter	1/60 (50) to 1 / 100,000 sec.
Gamma Correction	0.45
White Balance	Auto (ATW)
AGC	Automatic
BLC	Automatic
Current Consumption	80mA±10%
Working Voltage	DC 12V
Video Output	1.0 Vp-p Composite, 75Ω
OSD Function	Operated by Cable and Remote Control
Operation Temperature	-10℃ ~ 60℃ , Storage: -30℃ ~ 70℃
Dimension(mm)	φ280mm

