

# SMALL MIRROR CAMERA WITH OSD



## FEATURES

- Patent: The design of CCTV Camera behind the Mirror without pinhole on the surface
- Special Coating Technology
- Patent: OSD Function operated by Cable or Remote Control (optional) (Adjust the parameters of camera easily!)
- Apply to ATM machine, Bank, Counter, Bus, Car
- 1/3" Sony Super HAD II Color CCD Sensor

## SPECIFICATION

Model No.	CMXSH
Built-In Lens	4.3mm (Available for 6, 8, 12, 16mm Lens)
Color CCD	1/3" Sony Super HAD II Color CCD Sensor
Lens Angle	78°
System	NTSC / PAL
SYNC System	Internal
Number of Pixel	NTSC : 811 ( H ) x 508 ( V ) PAL : 795 ( H ) x 596 ( V )
Resolution	600 TV Lines
Minimum Illumination	0.1 Lux
S / N Ratio	More than 48dB
Electronic Shutter	1/60 ( 50 ) to 1 / 100,000 sec.
Gamma Correction	0.45
White Balance	Auto (ATW)
AGC	Automatic
BLC	Automatic (64 area set up by OSD)
Current Consumption	80 mA±10%
Working Voltage	DC 12V
Video Output	1.0 Vp-p Composite, 75Ω
Operation Temperature	-10°C ~ 60°C, Storage: -30°C ~ 70°C

