
FIRE SPRINKLER CAMERA





FEATURE

- 1/3" Sony Super HAD II Color CCD Sensor achieves impressive performance of high sensitivity
- Excellent Picture Performance with Hi-resolution (600 TVL)
- Apply to Home Security, Office, School, Supermarket, Restaurant, Government Building, Bank, Hotel, Parking Lots



SPECIFICATION

Model No.	FSH		
Lens	4.3 mm		
Color CCD	1/3" Sony Super HAD II Color CCE) Sensor	
System	NTSC / PAL		
SYNC System	Internal		
Number of Pixel	NTSC:811(H)x 508(V) PAL:795(H)x 596(V)		
Resolution	600 TV Lines		
Minimum Illumination	0.1 Lux		
S / N Ratio	More than 48 dB		
Electronic Shutter	1/60 (50) to 1 / 100,000 sec.		
Gamma Correction	0.45		
White Balance	Auto (ATW)		
AGC	Automatic	A	\bigcap
BLC	Automatic		
Current Consumption	80mA ± 10 %		35mm
Working Voltage	DC 12V		
Video Output	1.0 Vp-p Composite, 75Ω	The seals and	90mm
Scanning Frequency	15.734 KHz (H), 59.94 Hz (V)	°	₩ 40 mm 40
D/A Bit	10 D/A Bit	₩ ₩	
Operation Temperature	-10°C∼60°C	30mm ▲ 80mm	

Designs and specifications are subject to change without notice.