

# 2.0 Megapixel IP Box Camera



**LC-7513**

**2.0 Megapixel / Day & Night / H.264**



APPRO's LC-7513 is a high performance Fixed Network Camera which is equipped with a 2.0 megapixel CMOS sensor and a resolution of up to 1920x1080.

## ● 2.0 Megapixel

The LC-7513 offers to show you video feed with a large field of high resolutions at 2.0 megapixels that provide you with clear images in great detail.



VGA

2MP

## ● H.264 compression

Currently, the H.264 is the most common and dynamic video compression format and a powerful compression codec which delivers superior image quality at a low bit rate.

## ● Customize to suit the light

Our scheduled scenario settings customize exposure modes for your needs, adjusting your cameras to the differences in the varying strengths of light available at all hours in any given site. This enables ideal surveillance for all sites anywhere, from street traffic through shopping malls to buildings and office interiors.

## Features

- Adopts TI TMS320DM368 digital media processor.
- 1/2.7" OmniVision 2M CMOS sensor.
- Simultaneous H.264, MPEG4, and MJPEG video compressions.
- Three multi-profile applications: Selectable resolutions, frame rates, qualities, and compressions.
- Min. Illumination: color 0.2 lux at F1.2.
- Two-way audio.
- Advanced motion detection (512 zones, Sensitivity: 0~100 %).
- Built-in SD / SDHC card slot for schedule and alarm recording.
- Supports ONVIF.
- Full range of power options: DC 12V / AC 24V / PoE (IEEE 802.3af).

# 2.0 Megapixel / Day & Night / H.264 IP Box camera LC-7513

## SPECIFICATIONS

### Camera

- Image sensor: 1/2.7" OmniVision 2M CMOS sensor.
- Lens: CS-mount.
- Minimum illumination: Color: 0.2 Lux @ F1.2.;  
B/W: 0.01 lux@F1.2.
- IR cut filter.
- Day & Night: Auto/ Day/ Night/ Schedule.

### Image

- Video Compression: H.264 / MPEG4 / MJPEG.
- Resolution:
  - Aspect ratio:  
"4:3": 1440x1080, 1280x960, 1024x768, 800x600,  
640x480, 480x360, 320x240, 176x144.
  - "16:9": 1920x1080, 1280x720, 800x450, 640x360,  
480x270, 320x176, 176x144.
- Video streaming:
  - Simultaneous H.264, MPEG4, MJPEG.
  - Multi-profile: resolution / compression / frame rate /  
video quality.
- Profiles: 3.
- Frame rate:  
NTSC: Maximum 30FPS (1920x1080).  
PAL: Maximum 25FPS (1920x1080).
- Image settings:
  - AGC, Exposure Time, Mirror, Flip, White Balance,  
Brightness, Contrast, Saturation, Sharpness,  
Privacy masks.
- Exposure Mode:
  - Indoor, Outdoor, Night, Low-Noise, Moving,  
Customize 1~3, Schedule.
- Video management software: SDK, including HTTP-  
API / ActiveX / ONVIF.

### Audio

- Audio streaming: Two-way.
- Audio bit rate: G.711u 64kbps / G.726 32kbps.
- S/N ratio: More than 58dB.
- Inputs / outputs: 1 x input / 1 x output(3.5mm earphone  
jack).

### Network

- Security: Multi-level password protections, IP address  
filtering, HTTPS encryption, User access log.
- Protocols: IPv4, HTTPS, HTTP, TCP, UDP, RTP/RTCP/  
RTSP, DHCP, NTP, FTP, SMTP, UPnP, ICMP, ARP,  
DDNS, PPPoE, SAMBA.
- Users: Access by 10 simultaneous users.
- Firmware update: SD card / HTTP.

### Alarm

- Recording: SD card, SAMBA, FTP.
- Pre-alarm recording.
- Advanced motion: (512 zones, Sensitivity: 0~100 %).
- Trigger: Motion detection, Schedule, Alarm input,  
Ethernet loss, Network/Remote digital alarm input.
- Notification: SD card recording, SMTP, FTP, HTTP,  
alarm output.

### Connectors

- RJ-45: 10BASE-T/100BASE-TX.
- GPIO: Push-in: 1 x alarm input / 1 x alarm output / 1 x DC  
output(DC 12V) / 1 x Ground / 2 x RS-485.
- Earphone jack : 2 x 3.5 mm(1 x Audio in [mic. in / line in],  
1 x Audio out).
- DIP Switch: 1. AES / 2. DC iris / 3. DHCP / 4. Static IP.
- Iris: DC IRIS.
- Reset: Reset for factory default.
- Local storage device: SD / SDHC card slot.

### General

- LED indicators: Power / Network / SD card.
- Power:
  - DC 12V (DC power jack) Approx. 4.8 W.
  - AC 24V (2pin terminal block) Approx. 6 W.
  - PoE: Approx. 6 W, IEEE 802.3af compliant class 2.
- Power consumption:  $\leq 6$ W.
- Processors: TMS320DM368.
- OS: Linux 2.6 kernel.
- Operating conditions: 0°C to 50°C(32°F to 122°F).
- Approvals: CE, FCC, RoHS, C-Tick.
- Dimensions (HxWxD): 56 x 68 x 125 mm.
- Accessories included:
  - Installation Guide.
  - CD x 1 ( includes User's Manual ).
  - Power adapter: (Input: AC 100-240V , 50/60Hz, Output:  
DC 12V, 1A).
  - USB cable x 1.

\*Design and specifications are subject to change without notice.

APPRO TECHNOLOGY INC.



Taiwan Headquarter  
13F, No. 66, Zhongzheng Rd., Xinzhuang Dist., New Taipei City, Taiwan.  
Tel : 886-2-8992-1177 Fax : 886-2-8992-0077  
E-mail : appro@aprotech.com  
Web site:www.aprotech.com

Office in U.S  
1180 Miraloma Way Suite E, Sunnyvale, CA 94085.  
Tel : 1-408-720-0018 Fax : 1-408-720-0019  
E-mail : approu@aol.com  
Web site:www.appro-us.com

www.aprotech.com

**APPRO**<sup>®</sup>  
TECHNOLOGY